









Floodlights

Performance




Calinor EVO

Calinor EVO Floodlight PIR Warm White 20W Code: ACAE20/1/WW/B/PIR








Category

Application

Specification



Commercial, Industrial, Outdoor, Retail

PRODUCT FEATURES

- Compact, slim and robust designed LED floodlight suitable for residential and commercial applications
- Toughened microprism glass for visual comfort, uniformity and durability
- Pre-wired with 1 metre of rubber insulated cable for ease of installation and easy integration with Floodbox accessory
- Polycarbonate spike accessory allowing installation into lawn and garden applications
- Polycarbonate front trim provides excellent corrosion resistance
- Bracket design allows installation without removing mounting bracket
- Breather gland acts to minimise risk of water ingress
- PIR versions complete with manual override facility

GENERAL INFORMATION		
Wattage	20W	
Lumens Delivered	2000lm	
Lm/W	103lm/W	
Beam Angle	100	
CRI	80	
CCT	3000K	
Input	220/240V	
Operating Temp	-15°C - 40°C	
SDCM	6	
Energy efficiency class	Е	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Surface	
Lumen Depreciation	L80 69,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	175 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750