## **Prism Pro Fire Rated Downlight**
















- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm<sup>2</sup> + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations
- Wide 65° beam angle for increased light distribution





56.5

















Available bezel options Chrome, Satin Chrome and Black

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 35°C	L70 60,000	Ra 80	6	65°	1	IP65

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR
APRIP/1	CCT Selectable	5/7W	2700K/3000K/ 560lm(4000K 5W)		110lm(4000K 5W)	25
APRIP/1/MP1	CCT Selectable Multipack x 10	5/ / ٧٧	4000K/6000K	740lm (4000K 7W)	105lm (4000K 7W)	20

\* UGR Value based on (4H - 8H)

CODE (ACCESSORIES)	DESCRIPTION
APRILEDPBZ/CH	Chrome Trim Bezel
APRILEDPBZ/SC	Satin Chrome Trim Bezel
APRILEDPBZ/BLK	Matt Black Trim Bezel
ACFLP/3	LED Emergency Lighting Pack

	Controlled beload on (in the only
CODE (ACCESSORIES)	DESCRIPTION
APRILEDP/CP/MW	Converter Kit Matt White
APRILEDP/CP/CH	Converter Kit Chrome
APRILEDP/CP/SC	Converter Kit Satin Chrome
APRILEDP/CP/BLK	Converter Kit Black