









Battens and Weatherproofs

Hospitality, Industrial, Retail

Performance




Tornado EVO

Tornado EVO CCT Multi Wattage 1200mm Code: ATORE4/1








Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- $\bullet~$ LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

GENERAL INFORMATION		
Wattage	20W/40W	
Lumens Delivered	3100lm - 6200lm (4000K)	
Lm/W	160lm/W (4000K)	
Beam Angle	120	
CRI	80	
CCT	4000/5000/6500K	
Input	220/240V	
Operating Temp	-20°C - 40°C	
SDCM	6	
Energy efficiency class	D	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Surface, Suspended	
Lumen Depreciation L70 B50	L70 B50 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	80 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

