


DATASHEET



TNXTEM

TENAX 230V Wattage and CCT Adjustable Emergency LED Gear Tray

www.mlaccessories.co.uk



MLA PART CODE	TNXTEM
DESCRIPTION	TENAX 230V Wattage and CCT Adjustable Emergency LED Gear Tray
NET WEIGHT (KG)	0.315
DIMENSIONS (MM)	Length - 235 Width - 235 Projection - 28
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP20
WATTAGE (W)	10/15/20
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1360/1480/1405, 1905/2090/1960, 2345/2630/2415
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	151/147/141
LUMENS EMERGENCY MODE (LM)	125
CIRCUIT WATTAGE (W)	9.7/14.3/18.6
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.049/0.067/0.085
DISPLACEMENT FACTOR	>0.7
SVM	0.69
PST-LM	0.36
L70B50 LIFESPAN (HRS)	40,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No
OPERATING TEMPERATURE	-5~35°C

INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18W OUTPUT CURRENT - 360mA POWER FACTOR - 0.96 EFFICIENCY FULL LOAD - 0.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 85°C
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270894677

Date Created: 20/03/2024 15:16

