



ADL12.7

Term Tech Adhesive Lined Heatshrink Tubing 3:1 Shrink Ratio 12.7mmØ Black 1200mm Length



The Termination Technology range of Adhesive Line Heatshrink is manufactured from Crosslinked Polyolefin to be robust in a range of environments. Supplied in sturdy 1200mm lengths with an inner adhesive that bonds to a wide range of materials. With a high shrink ratio of 3:1 each size can be utilised more effectively to cover a larger range of applications, effectively making the product more efficient and reducing waste. Medium walled adhesive lined Heatshrink is also available for more heavy duty applications.

Technical Data

Colour and Material

Material	Crosslinked Polyolefin
Colour	Black

Dimensions

Product Length (mm)	1200
---------------------	------

Durability

Fungus Resistance	No Growth ASTM G-21
-------------------	---------------------

Electrical Ratings

Dielectric Strength (kV/mm)	22
Volume Resistivity (Ohm/cm)	10^{14}

Physical Attributes

Flexibility	Flexible
Tensile Strength (Mpa)	15
Maximum Elongation (%)	400
Adhesive Lined	Yes



Specific Gravity (g/cm ³)	1.25 ASTM D-792, ISO R1183
Water Absorption (%)	0.15 VDE 0472

Temperature and Fire Information

Continuous Operating Temperature (°C)	-55 to +110
Shrink Temperature (°C)	+95
Fire Rating	Flame Retardant
Flammability Testing	ASTM D-876

