

Product Features:

- IP44 rated
- Low cost energy saving alternative to compact fluorescent fittings
- Edge-lit low profile ideal for installations with limited recess space (25mm) and shallow ceiling voids
- Plug and play remote driver for easy installation (40mm space required)
- Separate triac dimmable driver available
- Life not affected by frequent switching e.g. when used with occupancy controls
- 1.5kV surge protected
- 3 year warranty






Slim-Fit[™] 18W IP44 Round Low Profile LED Downlight


Product Specs:

Technology	LED	Lamp Base	None
Input Voltage	100~240V AC	LED Chip	SMD 2835
Number of LEDs	90	Positional Adjustment	Fixed
Input Frequency	50/60HZ	Lifetime L70 (hrs)	25000
Power Factor	0.9	Dimmable	No
Luminaire Distribution	Accent	Positional Adjustment	Fixed
IP Rating	IP44	IK Rating	IK07
SDCM	6	Operating Temp	40°C
Overall Diameter (mm)	225	Cutout Diameter (mm)	206
Recess Depth (mm)	40	Weight (Kg)	0.440

Line Drawing



Polar Curve



SKU Table and Ordering:

Cat No.(SKU Code)	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
EN-PL18B/30	18	3000	1100	61.11	110	White
EN-PL18B/40	18	4000	1200	66.67	110	White
EN-PL18B/65	18	6500	1300	72.22	110	White

Compliance & Approvals:





Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.