## **X**nightsbridge

## **DATASHEET**




## **BL5BK**

230V IP65 5W LED CCT Adjustable Surface Mount

**Brick light - Black** 

www.mlaccessories.co.uk



| MLA PART CODE                 | BL5BK   |
|-------------------------------|---|
| DESCRIPTION                   | 230V IP65 5W LED CCT Adjustable Surface Mount Brick light - Black |
| NET WEIGHT (KG)               | 0.35  |
| FINISH                        | Black   |
| DIFFUSER                      | Opal  |
| DIMENSIONS (MM)               | Height - 100<br>Width - 235<br>Projection - 32                    |
| CONSTRUCTION                  | Construction - Polycarbonate                                      |
| CLASS                         | II  |
| IP RATING                     | IP65  |
| WATTAGE (W)                   | 5   |
| LAMP TECHNOLOGY               | SMD LED   |
| LAMP INCLUDED                 | Yes   |
| LUMENS (LM)                   | 495/530   |
| LUMENS LIGHT SOURCE ONLY (LM) | 820   |
| LUMEN TOLERANCE               | 5%  |
| EFFICACY (LM/W)               | 152.9   |
| CIRCUIT WATTAGE (W)           | 5.38  |
| ССТ                           | 3000/4000K  |
| LIGHT COLOUR                  | CCT   |
| CRI                           | >80   |
| SDCM                          | <6  |
| RUNNING CURRENT (A)           | 0.025   |
| DISPLACEMENT FACTOR           | >0.9  |
| SVM                           | 0.001   |
| PST-LM                        | 0.147   |
| BEAM ANGLE (DEGREES)          | 110   |
| LIFE SPAN (HRS)               | 30,000  |
|                               |   |





## **X**nightsbridge

| 60,000  |
|---|
| Yes   |
| No  |
| -20~50°C  |
| 230V 50Hz   |
| 20mm rear and side  |
| Blind grommet   |
| DRIVER TYPE - Constant Current MAX. OUTPUT - 5W OUTPUT VOLTAGE - 133V OUTPUT CURRENT - 38mA POWER FACTOR - >0.9 EFFICIENCY FULL LOAD - 90 AMBIENT TEMPERATURE (Ta)5 - 50°C CASE TEMPERATURE (Tc) - 65°C |
| 3year(s)  |
| BS EN 60598   |
| China   |
| Yes   |
| 5056270824377   |
|   |

Date Created: 13/05/2022 14:15





