

JCEM002

Emergency Remote Pack

External Emergency Remote Pack Standard 2W IP20 LifePo4 battery

Features & Benefits

- Plug and play connectors for quick and simple installation
- For Skytile LED panels and JCC recessed products
- 2W maximum output
- LifePo4 battery
- 5 Year Warranty including battery



CLASS II



EMERGENCY



RATING



WARRANTY

General Information

Mounting

Recessed

Environment

Indoor

Suitable For Zones

Outside Zone 2

Product Group

Emergency Remote Pack

Product Range

Emergency

Trade Name

Emergency Range

Color Finish

Green

Product Shape

Rectangular

Overall Dimensions

234.2(L) x 49.2(W) x 36.7(H)

Light Source

LED

Product Weight(kg)

0.45

Additional Information

LED indicator cut out 20mm

Recommended Product Location

Ceiling voids(recessed applications)

Product Aperture Size

60mm

IP Rating

IP20

Origin of manufacturer

Made in China

Warranty

2 years standard warranty extends to 5 years when registered within the first year of purchase (5 years on batteries)(See Website for terms and conditions)

Operation Type

Maintained only

Lighting Product Type 1

Emergency Lighting

Lighting Product Type 2

Accessory

Electrical

Voltage Rating	220-240
Primary Running Current(Amp)	0.05
Inrush current(Amps)	7
Operating Frequency Hz	50/60Hz
Secondary running current(mA)	220-25
Luminaire Circuit Wattage	2W max Output
Class	II
Power Factor Correction	0.5
Input Electrical Connections	N(Neutral)E(Earth)Usw/L(Unswitched Live)Sw/L(switched Live) loop-in loop-out

Emergency Data

Load Voltage(DC)	9-75
LOR % in Emergency Mode	To calculate the LOR% please use the formula shown: 2.4W Power in EM mode ÷ Fitting Wattage (e.g. 10W) x 100 = LOR % (2.4 ÷ 10 x 100=24%)
Inverter PFC	0.5

Battery Data

Battery Specification	LiFePO4 6.4V
Battery Type	Lithium Iron
Nominal Battery Current	1.8Amp
Charge Current	250mA
Recharge Time	24hrs
Battery Total Weight(kg)	0.084

Thermals

Insulation Coverage	Do not cover with insulation
Operating Temperature Range °C	0 to +50

Construction

Primary Material	Polycarbonate
------------------	----------------------

Packaging

Product carton overall dimensions(cm)	26.5(L)x12.5(W)x4.5(H)
Product Packaged Weight(kg)	0.56
Quantity Per Outer Carton	20
Outer carton(L)- cm	38
Outer carton(W)- cm	29
Outer carton(H)- cm	18
Outer carton Net weight- kg	11.2
Outer carton Gross weight- kg	11.7

Product Bar Code EAN-13 Number

5052544110054

Outer carton Bar Code ITF-14 Number

15052544110051

Standards & Approvals

Manufactured In Accordance To

BS EN 60598:2015, 2-22

CE Marked

Yes

UKCA Marked

Yes

Date code/Purchase order No.

Yes

WEEE Symbol

Yes

Certificate Of Conformity

Available on request

Accredited Members

LIA, ISO9001-2015, ISO14001-2015



