

# EARTH ROD PRO

For rapid Earth Rod installation

## EARTH ROD PRO RANGE

**Threads onto any standard earth rod**

**Bores through hard top layers and underground rock.**

**EARTH ROD MAX DRIVER**  
Attaches to your SDS drill

**EARTH ROD PRO DRIVER**  
Attaches to your SDS drill

**EARTH ROD DRILL BIT**  
Attaches directly to the earth rod

### SPECIFICATIONS

**Quality Standard:**  
All parts are produced in UK manufacturing facilities with an approved, certified Quality Management System compliant with ISO 901:2015.

**Threads:**  
All parts made concurrently on state of the art sliding head lathes to ensure perfect compatibility of 5/8" BSW threads with copper earth rods.

**Heat treatment:**  
Through-hardened to 45-55 HRC Rockwell, Strikes the perfect balance of toughness in hammer drilling applications.

**Brazing:**  
Copper-brazing carbide tips at 1100 degrees Celsius to ensure an ultra-strong bond between tip and steel for extreme durability in the toughest drilling applications

**Carbide Tip Specification:** European sourced 'Hammer-grade' Tungsten carbide tip designed to withstand hammer blows into the hardest of masonry substrates.


**Earth Rod Drill Bit**  
Standard Tip also available (without Carbide) for fast, economical installation into softer substrates.

**Drive Shanks:**  
Both our drive shanks are made to Bosch license specifications.

**Steel Specification:**  
High alloy content, chromium, nickel, molybdenum European steel.


### FAST AND EASY TO INSTALL

Remove your chosen Driver and Drill Bit from the packaging



Turn the Driver and Drill Bit onto each end of the earth rod and Insert the Driver into the SDS or SDS Max chuck

You can apply some grease to the shafts for easier removal



Using the SDS drill, drive the rod into the substrate to the required depth

