



DATA SHEET DOMESTIC SWITCH FUSE DP METAL

Catalogue Reference:-	DSF60M	-Fitted with a 60Amp fuse
	DSF80M	-Fitted with a 80Amp fuse
	DSF100M	-Fitted with a 100Amp fuse
	DSFNFM	-UN fused, 100A max

PRODUCT SPECIFICATION

The Wylex Domestic Switch Fuse units are available in 4 ratings 60A, 80A, 100A and a UN fused option.

The range is specifically designed to provide a compact and economical solution to make the installation and connection of sub mains or system extension easy for domestic and single phase commercial and industrial applications.

Unit Specification	IEC60947-3 BS EN 61439-3 * (*relevant clauses)
Fuse Specification	BS1361:1971 (incl amends 1, 2, 3)
Ratings	100A, 80A, 60A - class of operation gG
Switch information	Real contact position indicator, Padlocking facility for the “ off” position
Terminal Capacity L & N	16mm² min 35mm² max (3mm Allen Key)
Supply Torque Setting	2.3Nm
Earth Termination	10mm² min 16mm² max (2mm Allen Key)
Earth Torque Setting	Cage 0.7Nm, Terminal Bar 1.2Nm
Cable access	32mm dia knockout
Enclosure	1.0mm thick steel c/w overall door and low smoke & fume Epoxy paint finish white RAL9010
Dimensions	178mm Wide 302mm High 11mm Deep

Replacement Fuses	
Part Ref	Rating
DSF40FL	40A
DSF45FL	45A
DSF50FL	50A
DSF60FL	60A
DSF80FL	80A
DSF100FL	100A



Unrestricted Sales Telephone: 01543 455020

Telephone: 01543 438320

Email: wylex.technical@electrium.co.uk

Web: www.electrium.co.uk

WY-V01-2016